



PRODUCT DESCRIPTION

- Extremely quiet operation
- Outside operation temperature as low as -20°C
- Built-in back up electric booster for heating and hot water

TECHNICAL SPECIFICATIONS

Model	5kW	7kW	9kW	13kW	17kW
Output @ 35°C Flow/-5°C External	4.9	6.0	8.5	12.0	12.5
Output @ 55°C Flow/-5°C External	4.7	5.4	7.1	10.4	10.9
SCOP @ 35°C Flow	4.65	5.16	4.93	4.54	4.85
SCoP @ 55°C Flow	3.34	3.67	3.70	3.24	3.61
Fuse size Single Phase (Amps)	10	16	16	25	N/A
Fuse size Three Phase (Amps)	N/A	N/A	N/A	N/A	13
Sound Pressure Level (dBA)	39 ¹⁾	39 ¹⁾	40 ¹⁾	47 ¹⁾	45 ¹⁾
Sound Power Level (dBA)	47 ²⁾	47 ²⁾	48 ²⁾	55 ²⁾	53 ²⁾
Operating Temperature Range °C	-20 to +35	-20 to +35	-20 to +35	-20 to +35	-20 to +35
Refrigerant Type	R410A	R410A	R410A	R410A	R410A
Required Flow Rate (L/min)	20	20	20	34	35
Dimensions H x W X D (mm)	1380 x 930 x 440	1380 x 930 x 440	1380 x 930 x 440	1695 x 1122 x 545	1695 x 1122 x 545
Weight (kg)	106	107	114	182	193
MCS Number Single Phase	011-1W0122_01	011-W0123_01	011-W0124_01	011-W0125_01	N/A
MCS Number Three Phase	N/A	N/A	N/A	N/A	011-W0126-01

1) Sound power level tested at a distance of 1m dB (A)

2) Sound level in accordance with EN12102

Indoor Unit Dimensions H x W x D (mm)	700 x 495 x 386
Indoor Unit Weight (kg)	32



7 year warranty as standard